

Negative Hydrogen Ion Sources for Fusion Tutorial for NIBS 2020

Ursel Fantz, Dirk Wunderlich, Max-Planck-Institut für Plasmaphysik, Garching
on behalf of the ITER NBI contributors



ITER, France



RFX, Italy



QST, Japan



NIFS, Japan




IPR, India



IPP, Germany

Fusion – The energy source of the sun

Hydrogen \Rightarrow Helium




15 mill. °C

1.4 mill. km



on Earth: Hydrogen isotopes \Rightarrow Helium



Fusion on Earth needs 10 times higher temperature as in the sun!

The fusion experiment ITER



Largest multinational scientific mission.

1985: Project starts

2006: ITER Agreement officially signed

2019: > 65% ready


To demonstrate the scientific and technological feasibility of fusion power for peaceful purposes.

To produce a burning plasma.

$Q > 10$ for 400 s ($Q > 5$ for 3600 s)

Output (fusion power): 500 MW

Input (heating power): 50 MW



Size: 24 m diameter, 30 m height
Weight: 23 000 tons (3 x Eiffel tower)


NBI: Neutral Beam Injection of energetic neutral atoms (H or D)

To achieve with ECRH and ICRH the plasma temperatures and profiles for DT phase

↑
Electron

↑
Ion cyclotron resonance heating

Installed power
ECRH: 20 MW
ICRH: 20 MW
NBI: 33 MW



HNB: heating
DNB: diagnostic
neutral beam

NBI Functions


Heating Current drive Plasma rotation Diagnostics

2 + 1 HNB beam lines

1 DNB beam line sharing port with HNB-1


ITER NBI systems and their requirements

Heating beams (50% EU, 50% JA) : **33 MW** (2 injectors) for 3600 s, **1 MeV Deuterium**, **870 keV Hydrogen**
Diagnostic beam (100% IN): **2.2 MW**, **100 keV Hydrogen**, 3s ON/20s OFF 5Hz



Why negative hydrogen ions?

Neutralisation efficiency at a beam energy of 1 MeV D




Negative ion based systems make high energy range accessible

JT-60U / JT-60SA, LHD

$U_{acc} > \approx 150 \text{ kV}$, $j = 20 \text{ mA/cm}^2$

increase of
source size




Positive ion based systems are routinely operating world wide

JET, AUG, TFTR, DIII-D, JT-60U, ...

$U_{acc} < \approx 100 \text{ kV}$, $j \approx 200 \text{ mA/cm}^2$


Concept of ion sources – Arc sources and RF-driven sources

Arc sources




- ▶ Hot cathodes (2000 – 3000 K)
- ▶ DC voltage (≈ 100 V)
- ▶ Arc current (1000 A)

Filaments require regular maintenance




RF sources



- ▶ Inductively driven source
- ▶ RF power supply (≈ 100 kW)
- ▶ RF frequency 1 MHz


Long lifetime, routine operation for positive ions at AUG

RF concept chosen by ITER in 2006




Multi-aperture grid system (AUG)
774 apertures, 8 mm in diameter
3 grids for acceleration & focussing

NBI systems at LHD at NIFS, Japan



	negative	positive
Beam energy [keV]	190	80 & 90
Injection power [MW]	5.5 - 6.9	9
Pulse length [sec]	10 (max)	10 (max)
Beam divergence [mrad]	5	11





Arc sources, operation mostly in hydrogen

K. Tsumori, *Fusion Sci. Tech.* **58**, (2011) pp.489

Towards 100 s of H⁻/D⁻ beams with 500 keV, 22A (130 A/m²)

Based on arc sources



Achievement of beam acceleration
500 keV, 156A/m²,
118 s
By using 1/8 scale ion source



Achievement of H⁻ ion production
15 A for 100 s
→ under progress



Large ion source & accelerator is combined, and starts from 2023.

R&D for the ITER ion source – a size scaling route

Cs evaporation

H^- , H^+ , H_2^+

ITER beam lines: HNB, DNB
NBTF: SPIDER, MITICA

800 kW RF power coupled by 8 drivers to illuminate 1280 apertures arranged in 16 beamlet groups

BATMAN Upgrade @ IPP

ELISE @ IPP

20 A


40 A

Source area of $1 \times 2 \text{ m}^2$

Prototype source ~ 2 A


SPIDER @ 100 keV

started in June 2018



MITICA @ 1 MeV


starts in 2023



110 m

Full ITER beam line

NBTF
Neutral Beam Test Facility




4 m

Critical challenges:

- ▶ Extraction of 40 A negative ion beam from a large-size RF source
- ▶ Acceleration 1 MeV with accurate beam optics
- ▶ Development of high-voltage, gas-insulated transmission lines
- ▶ Voltage holding (1 MV) over pulses of 3600 seconds



The beam source of MITICA (full size HNB prototype)




The 1 MeV acceleration R&D at QST, Japan



Vacuum-insulated beam source for ITER



Vacuum insulation design by using meter-class large grid



By using 5-stage accelerator, long pulse MeV-class beam acceleration tests over 100 s – 1000 s


Proof-of-Principle beam acceleration test to support MITICA/NBTF and the final design for ITER

ELISE is dedicated to

- ▶ Provide input for design, commissioning and operation of ITER NBI systems
- ▶ Demonstrate ITER parameters in large sources
 - Extracted currents (ions and electrons)
 - Beam homogeneity
- ▶ Develop most efficient source operation scenarios

Parameter and targets

Isotope D ⁻ (H ⁻)
RF power = 2 x 150 kW in 4 drivers
$A_{\text{ex}} = 1000 \text{ cm}^2$, uniformity > 90%
$I_{\text{ion,ex}} = 29 \text{ (33) A}$, $I_e/I_{\text{ion}} < 1$ at 0.3 Pa
$U_{\text{tot}} = 60 \text{ kV}$, $U_{\text{ex}} < 12 \text{ kV}$
Plasma: 3600 s
Beam: 10 s every ~150 s (HV supply)



ELISE – A half size ITER source

First plasma and beam: Feb. / Mar. 2013




ELISE is dedicated to

- ▶ Provide input for design, commissioning and operation of ITER NBI systems
- ▶ Demonstrate ITER parameters in large sources
 - Extracted currents (ions and electrons)
 - Beam homogeneity
- ▶ Develop most efficient source operation scenarios


Parameter and targets

Isotope D ⁺ (H ⁺)
RF power = 2 x 150 kW in 4 drivers
$A_{\text{ex}} = 1000 \text{ cm}^2$, uniformity > 90%
$I_{\text{ion,ex}} = 29 \text{ (33) A}$, $I_e/I_{\text{ion}} < 1$ at 0.3 Pa
$U_{\text{tot}} = 60 \text{ kV}$, $U_{\text{ex}} < 12 \text{ kV}$
Plasma: 3600 s
Beam: 10 s every ~150 s (HV supply)




The grid system

Three grids




GG **EG** **PG** **BP**
Bias Plate
Plasma
Extraction
Grounded Grid

Two segments





PG and inner surfaces of the ion source are coated with molybdenum to avoid Cs interaction with Cu.

Extraction grid



EG
1-2 mm wall between vacuum and 16 bar water
grooves for electron deflecting magnets


altering direction from row to row



Power density of 32 MW/m^2 by co-extracted electrons

Present status – Source performance

Extracted current density [A/m²]



Main challenges


- ▶ Cs management
- ▶ Long pulses
- ▶ Co-extracted electrons

Typical long pulse behaviour

Source performance is probed by short pulse extraction of 10 s every 3 min

- ▶ **Stable** negative ion current density (within 10%)
- ▶ Strong **temporal dynamics** of co-extracted electrons


Interlock of extraction grid is set to 125 kW/segment although designed for 200 kW (ITER: 600 kW for all 4 segments)



Requires careful Cs conditioning and measures to suppress co-extracted electrons


Achievements of ELISE in 2018 – Towards ITER targets

Parameter for hydrogen (almost*) achieved in consecutive pulses



* due to technical limitations (HV power supply & RF generators)

Footprint of beam at calorimeter



Demonstration of first operational phase at ITER (up to 2035)

Strong isotope effect in terms of co-extracted electrons


Transition from hydrogen to deuterium at identical source parameters

- ▶ Drastic increase of **co-extracted electrons**
- ▶ Strong increase of **Cs density** close to plasma grid

at almost the same **ion current density**



In general: **co-extracted electrons**

- ▶ are factor 2 – 4 higher in D
- ▶ **limit the source performance**
- ▶ require more Cs (~ factor 2)



One of the key elements – The Cs dynamics

Simulation of the average Cs flux Three phases: vacuum, plasma, extraction




- ▶ **Back streaming** pos. ions sputter Cs and provide additional Cs
- ▶ **Continuous extraction** \Rightarrow still not sufficient to stabilize Cs flux
- ▶ **Unlimited Cs reservoirs** in the back-plate: higher and stable flux

Insights by CW extraction
at SPIDER (soon at ELISE)

Diagnostics for beam divergence and homogeneity


Arrangements of apertures

640 apertures, 8 beamlet groups



Beam emission spectroscopy

20 lines of sight




Vertical array of 16 LoS

Horizontal array of 4 LoS

IR calorimetry

2D fit on IR footprint



Grid system




2.7 m

3.5 m

Beam characterisation: group of beamlets - single beamlet


ITER requires a divergence of < 7 mrad (0.4°) in the core of a single beamlet

ELISE grid system: simulation give a divergence of $0.6 - 0.8^\circ$ (3 grids with max. 60 kV acceleration)




Horizontal LoS sees zig-zag deflection caused by deflection field (EG magnets)

Single beamlet lower than group of beamlets
Agreement with simulation




Versatile diagnostics of plasma and beam for fundamental understanding



H α image of H $^-$ extracted distribution

5 x 3 beamlet pattern on a CFC tile monitored with infrared camera




K. Ikeda *et al.*, *New J. Phys.* **15** (2013) 103026
 S. Geng *et al.*, *Fusion Eng. Des.* **121** (2017) 481




Roadmap : Beam (operational experience) and technology development in parallel Learning curve on 3 test beds : ROBIN, TWIN, INTF

ROBIN TEST BED




before and
after Cs cleaning




- ▶ 27 mA/cm² H⁻ beams @ 25 keV
- ▶ High Cs consumption (impurity control)
- ▶ e⁻/H⁻ > 1
- ▶ Experiments restarted after cesiated source cleaning

TWIN TEST BED



- ▶ Plasma production exp. initiated (50 kW two drivers)
- ▶ RF generator problems
- ▶ Accelerator system under proc.

ITER diagnostic beam developed at IPR, India




INTF @ ITER-India lab

Protoype DNB beam line

Unique 21.6 m path length to establish beam parameters and transport

- ▶ Several technologies developed enroute
- ▶ Components (DNB) under fabrication

Integration and commissioning : Q3 2021




Ion sources for fusion – Take-Home message

- ▶ Strong activities for ITER to make it a success!
- ▶ International coordination, only feasible with high commitment of participating institutes to ITER.
- ▶ Cutting edge physics and technology.
- ▶ We are on a good path with many contributions with distributed responsibilities and know-how.
- ▶ ITER is prepared with the NBI R&D activities worldwide. In fact, NBTF is the first ITER facility in operation.
- ▶ **Still huge challenges in front of us**
 - ▶ Achievement of Deuterium target values
 - ▶ Co-extracted electrons limiting the source performance
 - ▶ Cs management for large sources
 - ▶ 1 MeV holding and beam acceleration with accurate optics
 - ▶ Reproducibility and reliability



Fact Sheet

40 A, 1 MeV D⁻ for 1 h
46 A, 0.87 MeV H⁻
60 A, 100 keV H⁻ for DNB
800 kW RF (8 drivers), 0.3 Pa
7 Electrodes
15 beamlet groups
1280 beamlets



Many thanks to



Pierluigi Veltri



Gianluigi Serianni



Mieko Kashiwagi



Mahendrajit Singh



Katsuyoshi Tsumori



NNBI

and the respective teams

for providing valuable input to this contribution