

Budker Institute of Nuclear Physics



Design of the PANDA solenoid magnet

*Evgeniy E. PYATA^(a), Alexey V. BRAGIN^(a),
Mikhail A. KHOLOPOV^(a), Jost LUEHNING^(c),
Sergey G. PIVOVAROV^(a), Lars SCHMITT^(b),
Yury A. Tikhonov ^(a)

^(a) BINP, Novosibirsk, Russia


^(b) FAIR, Darmstadt, Germany

^(c) GSI, Darmstadt, Germany

PANDA solenoid magnet

The PANDA solenoid is designed to provide a magnetic field of 2 T with a uniformity of $\pm 2\%$ and radial magnetic field integral in the range 0 to 2 mm over the central tracking region. The magnet is characterized by a warm bore of 1.9 m diameter, a free length of 4 m and 22.4 MJ of stored energy.

Since PANDA is a fixed target experiment, the main technical challenge is the insertion of a warm target pipe vertically to the solenoid axis in correspondence with the interaction point located at 1/3 of the length of the solenoid. In order to meet the above requirement while satisfying the magnetic field homogeneity constraints, the magnet is split in 3 interconnected coil modules.



Artistic view of the solenoid magnet including detector systems

The main milestones of production of the PANDA solenoid magnet

The scope of delivery includes:


- Magnetic and engineering design of the magnet including tools and support;
- Production and delivery of the magnet (consisting of yoke, cold mass and cryostat, alignment components, proximity cryogenics, support frame and platform beams) and all tools;
- Power converter and quench protection and instrumentation.

Item	Date
Start contract	03/2017
Assembling of the solenoid at the BINP site	09/2022
Magnetic tests of the PANDA solenoid including safety system and electrical components at BINP (additional contract)	09/2023 - 05/2024
Assembling and tests at the FAIR site	
Assembling of the magnet at Darmstadt	06-10/2024
Acceptant tests at FAIR	11/2024
Installation of the PANDA solenoid magnet at worked position and final acceptance tests	01-05/2025

Magnetic field

Inside the cryostat the barrel of the electromagnetic calorimeter is housed which in turn contains the barrel DIRC detector, barrel Time of Flight, Straw Tube Tracker and Micro Vertex Detector.


In the region occupied by the MVD and the central tracker there are very stringent requirements for the magnetic field homogeneity. According to these, the absolute magnitude of the field shall not vary by more than 2% from the nominal field of 2 T over the whole tracker region, which is the main aim of the magnet design. Furthermore, the radial component of the magnetic field B_r has to be so low that any integral along z to the central tracker read-out plane, located at $z = -400$ mm, results in a value below 2 mm if started from any given point inside the central tracker.



Barrel DIRC
and ToF

MVD STT EMC

Magnetic field




Magnetic flux density distribution in the YZ-plane of the PANDA detector.

Magnetic measurements were made by our colleagues from JINR and presented in the TDR. The evaluation measurements made at BINP show good agreement with these results.

The TDR design has been revised by CERN for improved stability as well as simpler and cost optimized winding and assembly procedures. The optimization has been carried out considering the additional constraint that, due to the advanced design state of the other detector components, the solenoid layout could not be heavily modified. In particular, the changes applied to the size of the coil envelop and operating current had to be minimized.

As result the conductor and coil designs were developed at the present time.


Magnetic field



Magnetic flux density distribution in the YZ-plane of the PANDA detector.

Criteria	Absolute Value	Definition
Micro Vertex Detector		
Dimensions, longitudinal: $-0.25\text{m} < z < 0.2\text{m}$, radial: $0.0\text{m} < r < 0.12\text{m}$		
$\frac{\Delta B}{B_0} < 2\%$	$\Delta B := B(r,z) - B_0 $	$B_0 :=$ nominal field, i.e. 2 T $B(r,z) :=$ field at any point in given region
Central Tracker		
Dimensions, longitudinal: $-0.4\text{m} < z < 1.1\text{m}$, radial: $0.15\text{m} < r < 0.42\text{m}$		
$\frac{\Delta B}{B_0} < 2\%$	$\Delta B := B(r,z) - B_0 $	$B_0 :=$ nominal field, i.e. 2 T $B(r,z) :=$ field at any point in given region
$I_B(r, z_0) < 2\text{mm}$	$I_B(r, z_0) := \int_{z_0}^{-400} \frac{B_r(r, z)}{B_z(r, z)} dz$	$z_0 :=$ any z value in region $B_r, B_z :=$ radial, long. field components, resp.


Requirements to magnetic field for MVD and Central Tracker



Magnetic flux density distribution in the Central Tracker volume in the XZ and YZ planes.


Radial field integral in the Central Tracker volume in the XZ and YZ planes.

PANDA solenoid magnet, BINP responsibility




PANDA conductor

Rutherford cable, 8 strands, extruded in Al matrix




Longitudinal section of the cryostat with cold mass.



Cold mass cross-section.

Thickness (after cold work) at 300 K	mm	7.93	± 0.03
Width (after cold work) at 300 K	mm	10.95	± 0.03
Critical current (at 4.2 K, 5 T)	A	> 14690	
Critical current (at 4.5 K, 3 T)	A	> 16750	
Overall Al/Cu/sc ratio		10.5/1.0/1.0	
Aluminum RRR (at 4.2 K, 0 T)		> 600	
Al 0.2% yield strength at 300 K	MPa	> 30	

Conductor mechanical and electrical parameters.



Cross-section of the conductor.

Status of the PANDA conductor development/ procurement

8 pieces of the samples of PANDA conductor produced with different tools were tested for a shear strength. Results are 62,5 – 85,3 MPa. Specified value of a shear strength is ≥ 20 Mpa.





Photo of the samples of PANDA conductor



Scheme of shear strength measurement



Conductor.

Status of the PANDA conductor development/ procurement
BINP/ VNIINM Bochvar/ VNIIKP/ Saransk cable optic (SarKO)

Rutherford cable co-extrusion/ conklad in a pure Al

- Production 1000m Cu Rutherford cable for tests in SARKO - 03-04/ 2020 (in BINP)
Tests in SARKO, 1000m Cu Rutherford cable - 04-05/ 2021
- Contracts for PANDA NbTi strands production, VNIINM - signed 09/ 2020
- Production strands VNIINM for central coil - 09/2021
- Production strands VNIINM for up/downstream coils - 12/2021
- PANDA Rutherford cables production, VNIIKP
- for central coil - 12/2021
- for up/downstream coils - 03/2022
- Production PANDA conductor BINP/SARKO - 01 - 05/ 2022

Cryostat and cold mass of the PANDA solenoid magnet




Parameter	Unit	Value
Outside diameter	MM	2680
Inner diameter	MM	1900
Length	MM	3090
Magnetic field in coil	T	3
Current	kA	5
Stored Energy	MJ	22,4
Weight	t	14.5

Axial length variation [mm]	B_{peak} [T]	δ_{max} [%]	Int_{max} [mm]	F_{axial} [kN]
- 6	2.67	1.63	2.03	-36.9
- 3	2.67	1.65	2.07	-37.0
0 (nominal)	2.66	1.67	2.10	-37.1
+ 3	2.65	1.70	2.13	-37.2
+ 6	2.65	1.72	2.17	-37.2

Outer diameter of coils is 2200 mm,
length: two coils - 887 mm, one – 400 mm.

3D model PANDA solenoid.

Cold mass parts




3D model of the PANDA cold mass.

Results of the calculations of the Cryostat.



Results of calculation of the Cryostat.

Operation condition
($p=0.1$ Mpa, the weight of Cold mass is 57 kN, the initial tightening force is 3.7 kN)





Results of calculation of the Cryostat.



Operation condition
($p=0.05$ Mpa, the weight of Cold mass is 57 kN, the initial tightening force is 3.7 kN)





The maximum deformation is 0,1 mm.



The maximum equivalent stress is 45 MPa.




The maximum deformation is 0,08 mm.




The maximum equivalent stress is 26 MPa.

Scheme of fixation of the cold mass.




Cold mass is based into Cryostat with help suspensions and axis rods.
Material is Ti-5Al-2.5Sn

In the axial direction the Cold mass is fixed with help longitudinal rods. The diameter of longitudinal rods is 20 mm, the length is 2010 mm downstream side and 1120mm upstream side.






The diameter of suspension is 16 mm, the length is 840 mm.

In the radial direction the Cold mass fixed with help radial rods. The diameter of radial rods is 12 mm, the length is 720 mm.



Results of calculation of the radial rods.




Maximum radial decentering magnetic force of 51 kN.

The initial tightening force is 3.7 kN.

Temperature distribution 4,5-300K.


The equivalent stress of radial rods is ~120 MPa.



The maximum equivalent stress is 178 Mpa of the support blocks.

Diagram of position of the target's axis after cool down and max magnetic forces.

The maximal displacement of the Cold mass is 0,95 mm to upstream direction



Upstream side

Magnet position into the yoke.

Misplaced, cm	Lorentz force, t	Sesmic, t
+ - 0	4	+ - 1
+ - 2	14	+ - 1

Thermal loads of the cold mass

T=4.5 K	Thermal load, W
Radiation	2.2
Heat inflow to the cold mass supports	2.52
Conductor joints	<0.5
Gas load	0.5
Eddy current losses in the Al cylinder	11.5
Eddy current losses in the conductor	0.09
LHe vessel, tubing, valves, supports, wiring	3.3
Transfer line	9.7
Total (worked condition/extraction energy regime):	20.1/31.7

Thermal loads of the cold mass and thermal shields of the PANDA solenoid are summarized in Tables for operation conditions and in case of energy extraction during 2000 seconds.

Heat loads of 4.5K surfaces.


T= 60 K	Thermal load, W
Radiation	62.4
Heat intercepts of the coil supports	33.4
Shield supports	91.2
Gas load	2
Wires	1
Thermal screen, valves, supports	36.5
Transfer line	14.1
Total:	240.6

Heat loads of 60K surfaces

Thermal loads of the cold mass

Eddy current loss in the coil windings.

$$P = 2 \int_0^{d/2} dP = \frac{lh}{12} \frac{d^3}{\rho} \dot{B}_z^2$$




Eddy current loss in the casing.

$$P = \frac{V^2}{R_{casing}}$$

$$V = M \cdot \frac{dI}{dt}$$

- Eddy currents in a rectangular thin plate




- Eddy currents in the casing produce the main loss contribution during ramp and slow dump.
- The thin high purity Al strip in thermal contact with the cooling ribs ensures minimal increase of the cold mass temperature during current ramp up and slow dump of the magnet 2000 seconds.

Temperature distribution in the cold mass.

Cryogenic system


The cryogenic system of the PANDA magnet consists of a Control Dewar with helium vessel, transfer line and thermosyphon circulation loop. It is a self-regulating thermosyphon circulation flow system. A natural circulation loop is operated on the principle that a heat load on the channels of the heat exchanger produces a two-phase flow that is on average of lower density than the liquid phase. Homogenous model is used for the preliminary study for CMS detector solenoid, CERN.

The scheme has a cooling circuit that will work with liquid nitrogen when the solenoid magnet is moved to the assembly area.



PANDA solenoid cryogenic Process Flow Diagram.

Cryogenic system



12 parallel cooling
channels DN10

Liquid from the helium vessel of the Control Dewar will be fed through the forward pipeline and manifolds at the bottom of the support cylinder. From there, the liquid will be heated up in the tubes of the heat exchanger (a rib cage configuration) on the surface of the support cylinder.





The two-phase helium from the top manifolds returns back through the reverse pipeline to the upper part of the helium vessel.

Thermosyphon circuit.


Distribution box - Control Dewar.

Control Dewar includes:

1. Vessel for liquid helium (~480L);
2. Current leads;
3. Thermal shields;
4. Valves, instrumentation;
5. Vacuum shell;
6. Transfer line (Chimney) connecting the vacuum vessels of cryostat and control Dewar.




Scheme of location of the PANDA magnet in beam position and in assembling area



The magnet will be approximately 6 month in parking position of the assembling area for maintenance. In this position a forced helium circuit (83-100K) cooled by liquid nitrogen is foreseen.

The travel between the parking and the beam position will take less than a day, and the expected temperature should stay in an acceptable range for the cold mass.

PANDA magnet areas.



Dependence of temperature and thermal loads of the cold mass and thermal shield.

The maximal temperature of the thermal shield is estimated about 130K after 8 hours and the maximal temperature of the cold mass ≈ 35 K.



Assembling of the Yoke

Final machining 5 July 2020 1st control assembling 09/2020 2nd control assembling and FAT 12/2020
Installed 10 support for detectors of a laser tracker.


Built an axis of the yoke and 3D map of elements by a laser tracker.

Measuring surfaces of the octants and wings we can do correction each part of the frames and barrel part of the yoke.

We plan to install about 30 the same support to do assembly of the yoke more quickly and suitable/



PANDA magnet, bld. 13. Area for cryogenic and coils tests and measurements of a magnetic field



Conclusion

Name of item	Status of work
Yoke and frame	Produced
Cryostat of solenoid	Start production
Cold mass	Start production
Conductor purchasing	Development work, production strands
Control Dewar box	CDR
PANDA solenoid power cabling	Design is ready, production
Power supply and energy extraction system	Detail design is ready, Purchasing power supply and electrical components, production
Magnet safety system	in process
FAT	Preparation place for PANDA solenoid installation, procedures installation, development a flow scheme of connection KEDR-PANDA solenoid cryogenics



Thank you for your attention

